

# KUKA



Robotics\_Range



EN

A	Arctic version down to -30°C
CR	Suitable for clean rooms
CR lite	Robot with improved ISO class
CV	Covered
EX	For potentially explosive areas
F	Foundry version
HM	Hygienic machine
HO	Food-compatible lubricants
S	Speed
WP	Splash-proof

The technical data in the table apply exclusively to standard versions.

1) Refers to intersection of axes 4 and 5  
 2) Different axis data for ceiling-mounted variants  
 3) Only available in special versions  
 4) Complies with IEC 60601-1  
 5) Only available in selected countries

Types		Types	
Rated payload		Rated payload	
Rated supplementary load on arm Max. reach <sup>1)</sup> / Z-stroke		Rated supplementary load on arm Max. reach <sup>1)</sup> / Z-stroke	
Number of axes Positioning repeatability Weight (robot) approx.		Number of axes Positioning repeatability Weight (robot) approx.	
Mounting position		Mounting position	
Version (optional) Comments		Version (optional) Comments	
Axis data		Axis data	
Range	A1	A1	A1
	A2	A2	A2
	A3	A3	A3
	A4	A4	A4
	A5	A5	A5
	A6	A6	A6
	A7	A7	A7
A1		A1	
A2		A2	
A3		A3	
A4		A4	
A5		A5	
A6		A6	
A7		A7	
Velocity		Velocity	

KR 300 R2700-2 KR 210 R2700-2  
 KR 250 R2700-2 KR 150 R3100-2  
 KR 240 R2900-2 KR 150 R2700-2  
 KR 210 R3100-2 KR 120 R3100-2  
 KR 180 R2900-2 KR 120 R2700-2

**\_19**

KR 270 R3100-2 K  
 KR 210 R3300-2 K  
 KR 180 R3500-2 K  
 KR 120 R3900-2 K

**\_20**

KR 160 R1570 nano  
 KR 120 R1800 nano

**\_21**

KR 360 R2830

**\_22**

KR 500 R2830

**\_23**

KR 280 R3080

**\_24**

KR 420 R3330

**\_25**

KR 340 R3330

**\_26**

KR 40 PA

**\_27**

KR 700 PA

**\_28**

KR 300-2 PA

**\_29**

KR 470-2 PA

**\_30**

KR 1000 L950 titan PA

**\_31**

KR 120 R3500-2 P

**\_32**

KL 100

**\_33**

KL 250-3

**\_34**

KL 4000

**\_35**

LBR iiwa 14 R820  
 LBR iiwa 7 R800

**\_01**

LBR Med 14 R820  
 LBR Med 7 R800

**\_02**

LBR iiy 3 R760  
 LBR iiy 11 R1300  
 LBR iiy 15 R930

**\_03**

KR 3 D1200 HM  
 KR 3 D1200-2 HM

**\_04**

KR 6 R700 Z200-2  
 KR 6 R500 Z200-2  
 KR 12 R650 Z400/Z600  
 KR 12 R750 Z400/Z600  
 KR 12 R850 Z400/Z600

**\_05**

KR 4 R600

**\_06**

KR 10 R1100  
 KR 10 R900  
 KR 6 R900  
 KR 6 R700

**\_07**

KR 10 R1100-2  
 KR 10 R900-2  
 KR 6 R900-2  
 KR 6 R700-2

**\_08**

KR 10 R1440-2 arc HW-2  
 KR 8 R1640-2 arc HW-2  
 KR 6 R1840-2 arc HW-2

**\_09**

KR 8 R1440-2 arc HW E  
 KR 8 R1640 arc HW E  
 KR 6 R1840 arc HW E

**\_10**

KR 6 R1440-2 arc HW E  
 KR 6 R2010-2 arc HW E  
 KR 12 R1810-2 arc HW E

**\_11**

KR 22 R1610-2 KR 16 R1610-2  
 KR 20 R1810-2 KR 12 R1810-2  
 KR 16 R2010-2 KR 8 R2010-2

**\_12**

KR 20 R1810-1

**\_13**

KR 8 R2100-2 arc HW

**\_14**

KR 20 R2010 KS-F

**\_15**

KR 70 R2100 F  
 KR 50 R2500 F

**\_16**

KR 20 R3100

**\_17**

KR 70 R2100 F  
 KR 50 R2500 F

**\_18**



II Robots

Not valid for KR 3 D1200 HM



-  [kuka.com/contacts](http://kuka.com/contacts)
-  [facebook.com/kukaglobal](http://facebook.com/kukaglobal)
-  [youtube.com/kukarobotgroup](http://youtube.com/kukarobotgroup)
-  [twitter.com/kukaglobal](http://twitter.com/kukaglobal)
-  [linkedin.com/company/kukaglobal](http://linkedin.com/company/kukaglobal)

Details provided about the properties and usability of the products are purely for information purposes and do not constitute a guarantee of these characteristics. The extent of goods delivered is determined by the subject matter of the specific contract. No liability accepted for errors or omissions. Subject to technical alterations. © 2022 KUKA